



HUAWEI  
**HDU7511036V100R001ENGC01B124S**  
**P04 Version Upgrade Guide**



Huawei Technologies Co., Ltd.

All rights reserved



## Contents

<b>1</b>	<b>VERSION INTRODUCTION.....</b>	<b>2</b>
1.1	VERSIONS CAN BE UPGRADED.....	2
1.2	UPGRADE PREREQUISITE.....	3
1.3	UPGRADE FILES .....	3
<b>2</b>	<b>UPGRADE PREPARATION.....</b>	<b>4</b>
2.1	CHECK CURRENT UPGRADE ENVIRONMENT .....	4
2.2	CHECK THE CURRENT RUNNING VERSION .....	4
2.3	GET AND CHECK THE SOFTWARE PACKAGE.....	4
<b>3</b>	<b>UPGRADE OPERATIONS.....</b>	<b>4</b>
3.1	NORMAL UPGRADE OPERATIONS .....	4
<b>4</b>	<b>UPGRADE VALIDATE.....</b>	<b>7</b>
4.1	VERSION DATA AND MAIN FUNCTION .....	7
4.2	BASIC FUNCTION CHECK .....	7
<b>5</b>	<b>ERROR HANDLE .....</b>	<b>7</b>
5.1	ERROR 1 .....	7
<b>6</b>	<b>NOTES .....</b>	<b>7</b>
6.1	NOTES 1.....	7

## 1 Version introduction

### 1.1 Versions can be upgraded

APP version list	BOOT version list
APP-M2V100R001ENGC01B112	BOOT-M2-B100-20100201
APP-M2V100R001ENGC01B113	



APP-M2V100R001ENGC01B114	
APP-M2V100R001ENGC01B115	
APP-M2V100R001ENGC01B116	
APP-M2V100R001ENGC01B117	
APP-M2V100R001ENGC01B118	
APP-M2V100R001ENGC01B119	
APP-M2V100R001ENGC01B120	
APP-M2V100R001ENGC01B121	
APP-M2V100R001ENGC01B122	
APP-M2V100R001ENGC01B123	
APP-M2V100R001ENGC01B124	
APP-M2V100R001ENGC01B124SP01	
APP-M2V100R001ENGC01B124SP02	
APP-M2V100R001ENGC01B124SP04	

## 1.2 Upgrade prerequisite

The M2 handset software should be updated with the MICRO SD card.

## 1.3 Upgrade files

	File Name	File Size	Date	Usage
Host software	None			
Parameter, configuration files	None			
Update tools				
Others	UPDATE.APP  CustomizeEfs.bin  operator_cfgdata.cfg  usr_file_backup.cfg  usr_nv_backup.cfg	109 MB	2010-9-03	For M2 update:  Logo+Boot+APP+QCN



--	--	--	--	--

## 2 Upgrade preparation

### 2.1 Check current upgrade environment

SD card update: Make sure that the MICRO SD card is available and can be read and write.

### 2.2 Check the current running version

In the Idle screen, enter **\*2580** and press the **down** navigation key, the board information will be showed.

### 2.3 Get and check the software package

According to the chapter 1.3, check the software package date and the file size.

## 3 Upgrade operations

For testing user, please refer to section 3.1.

For product user (Only in product line), refer to section 3.2.

### 3.1 Normal upgrade operations

Step 1. A MICRO SD card of 256MB or more should be available. The MICRO SD card made by Sandisk, Kingstone, or Kingmax is recommended.

Step 2. Format the MICRO SD card. This operation is optional.

Step 3. Unzips the **HDU7511036V100R001ENGC01B124SP04.rar** (right mouse button on it and select 'Extract here').

Step 4. Obtain the unzipped file (subdirectory: \dload\\*.\* ) to be upgraded.


Step 5. Copy the dload folder (**with CUSTOMIZEEFS.BIN; operator\_cfgdata.cfg; UPDATE.APP; usr\_file\_backup.cfg; usr\_nv\_backup.cfg in it**) to the root directory of the Micro SD card.

Step 6. Insert the Micro SD card into the handset to be updated. **Please make sure**


that a valid SIM/USIM card is inserted.

Step 7. Make sure that the handset to be updated was powered on and being in idle state.


Step 8. Enter \*1673492846 and press the down navigation key to enter the engineering mode, then select “1”, “1”, “3” step by step as follow pictures.




Pic1



Pic2



Pic3



Pic4

Step 9. The handset will restart automatically and enter into the increment upgrade (upgrade the corresponding parameter) interface when the HUAWEI Logo shows.

Step 10. After the increment upgrade finished, the handset will restart automatically again and shows “Reset to factory setting”. The handset will switch off when reset factory setting successfully.

Step 11. Then the upgrade is finished successfully.



## 4 Upgrade validate

### 4.1 Version data and main function

In mobile idle screen, enter \*2580 and press the **down navigation key** to check whether the version information is the same as that of the release version. :

Boot version	BOOT-M2-B100-20100201
APP version	APP-M2V100R001ENGC01B124SP04-DebugNoLog
EFS version	EFS-M2V100R001ENGC01B124SP04-20100903

### 4.2 Basic function check

Switch on the handset, enter the idle screen, input a dial number and make a voice call, then press the red key to power off the handset.

## 5 Error handle

### 5.1 Error 1

During SD card upgrade, an “F” in red is displayed on the screen when an error occurs. Check whether there is a miss-operation, You can change another phone or SD card to do the test. You can also consult the contact person if necessary

## 6 Notes

### 6.1 Notes 1

To make sure that the power of the battery is enough to run the upgrade process. Maybe you can connect the handset with the charger or the USB data cable to provide power.